

ROGA DAQ16

ROGA Mobility package USB 2.0 System



HighSpeed
USB 2.0
400 MB/s

- USB 2.0 / 480MBIT
(USB 1.1/12MBIT COMPATIBLE)

- 16 analog input channels (16bit/500kHz max.)
- IEPE sensor supply (24V/4mA)
- 0.125V to 10V input range
- Individual preamplifiers



- 4 analog output channels (16bit/100kHz)
- Powerful DSP (255MIPS) for filtering, control etc.
- 24 digital I/Os
- Optional 24bit counter, timer,
- PWM, incremental encoder
- Free drivers for major application software

TECHNICAL DATA

ANALOG INPUTS

Number of inputs	16
Input impedance	1MΩ differential
Analog bandwidth	0 – 20 kHz (DC mode); 1Hz – 20 kHz/1dBAC, IEPE (low frequency version on request)
ADC sample rate	500/400kHz
Resolution	16 bit
Input voltage ranges	±0.125, ±1.25, ±2.5, ±5, ±10V
IEPE sensor supply	4 mA/24V
Maximum input voltage	±40V
Gain accuracy	0.2% typical

ANALOG OUTPUTS

Number of outputs	4
Sample rate	100kHz/ch.
Resolution	16 bit
Settling time	±20V / 10μ, ±1V / 1μ
Output ranges	0 – 10V, ±10V
Maximum current	5mA
Impedance	0.2Ω

DIGITAL INPUTS / OUTPUTS

Number of inputs / outputs	24
Type	LVC MOS, 5V tolerant
Maximum current	2.5mA
Number of counters	2
Resolution	24 bit
Modes	up/down, frequency, period
PWM channels	1
Resolution	24 bit
Frequency range	2Hz – 2.5MHz
Incremental counters	24 bit incremental 16 bit time stamp
Interpolation	1 / 2 / 4
Maximum frequency	20MHz
Dimensions	180mm (w) x 167mm (d) x 80mm (h)
Weight	2kg
Power Supply	Adapter 100V – 230V AC/ 5V DC (included)

With the introduction of the RogaDAQ 16 USB 2.0 data acquisition system, a new age of measurement technology begins.

The RogaDAQ 16 is an affordable multichannel IEPE solution. The USB 2.0 interface permits unrivalled portability. Hotplugging the data acquisition unit during operation has now become a reality. The compact and rugged measurement unit with its BNC connectors breakout boxes obsolete. Downward compatibility to USB 1.1 also permits to run this high performance measuring system with older hardware. Simplicity of integration, whether mobile or stationary, has reached a new level.

ANALOG INPUTS

The input signals are digitized using the multiplex method. All 16 channels may be used as differential or single-ended inputs. The maximum sampling rate is 500 kHz at 16 bit resolution (400 KHz for multiple channels). The maximum bandwidth per channel is DC to 22 KHz (higher bandwidth on request). In single-ended mode, AC coupling is also available and constant current sensor supply for IEPE-type sensors can be provided.

The input circuitry consists of a software programmable precision amplifier with gain 1/2/4/8/10/20/40/80.

The input voltage ranges are 0.125 V to 10 V in eight steps, either bipolar or unipolar. The highly flexible signal conditioning and connectivity make the RogaDAQ 16 the perfect choice for the majority of measurement applications.

Along with the analog lowpass filters the system can make use of integrated oversampling filters (up to 16x, depending on channel count and sampling rate) in order to improve rejection of noise, distortion and out of band signals. DSP-filters suppress undesired frequencies and distortions. Therefore the user gets clean data.

There is no need for any additional hardware. Signal degradation caused by cabling, contacts and add-on signal conditioners is avoided. The RogaDAQ 16 is a truly affordable and powerful platform for multichannel IEPE-sensor applications.

ANALOG OUTPUTS

RogaDAQ 16 offers four analog outputs. The output sampling rate is 100 kHz per channel at 16 bit resolution. The output voltage ranges are 0 V–10 V und ± 10 V. They can be used as generator outputs, monitoring outputs or for control loops. It is also possible to download data to RogaDAQ 16 and output it to the D/A converters time synchronized by the DSP.

TRIGGERS

There are several trigger options available: Level, edge, limit or window conditions. It is even possible to use mathematically processed data for triggering (e.g. steepness of slope). Trigger conditions can start or stop a measurement, set digital outputs or control analog outputs. Several trigger conditions can activate or deactivate each other. So a network of dynamic triggers is possible, automatically adjusting to the current condition.

DIGITAL INPUTS/OUTPUTS

There are 24 digital inputs / outputs available. Any of these ports may be individually controlled by the DSP as input or output.

The digital inputs optionally support counter, pulse width, period length or frequency counter. Incremental encoders can also be supported on request.

The outputs can optionally be used for PWM signals with a resolution of 100ns and output frequencies between 2 Hz and 2,500,000 Hz with zero pulse discontinuities. Modulation of frequency and pulse width is supported at the same time and independently. It is fully transparent to the user, who only specifies a frequency and pulse width in percent.

SOFTWARE

One of the most important criteria for modern measurement systems is software support. Even the most powerful hardware is useless without respective drivers.

RogaDAQ 16 uses an optimized concept which ensures extensive application software support and easy adoption to new software environments.

Besides free of charge drivers for most common measurement applications like EVApro, DIAdem, LabView or DasyLab, further application programs are available. Custom driver support is possible on request.

SOFTWARE AND DRIVER UPGRADES

The most recent versions of drivers, programming interface and software are obtainable through ROGA-Instruments.

